

RC422

符合或超过EN856 4SP

Meets or Exceeds EN856 4SP



脉冲次数为标准的2倍

Impulse cycle exceeds the standard by 2X

产品特点

- 满足或超过EN856 4SP标准
- 软管脉冲次数为标准的2倍，获得更长的使用寿命
- 软管重量更轻
- 产品尺寸稳定

Product Features

- Meets or Exceeds EN856 4SP
- Impulse cycle exceeds the standard by 2X, and extending the product life.
- Lighter in weight
- Stable size

型号 Part No.	公称通径 DN mm NB inch		内径 I.D. mm in		外径 O.D. mm in		最大工作压力 Max.Working pressure bar psi		爆破压力 Min.Burst pressure bar psi		最小弯曲半径 Min.bend radius mm
RC422-04	6	1/4	6.4	0.25	17.6	0.69	450	6530	1800	26120	150
RC422-06	10	3/8	9.5	0.37	20.4	0.80	445	6455	1780	25820	180
RC422-08	12	1/2	12.7	0.50	23.3	0.92	415	6020	1660	24080	230
RC422-10	16	5/8	15.8	0.62	26.9	1.06	350	5075	1400	20300	250
RC422-12	19	3/4	18.7	0.74	31.1	1.22	350	5075	1400	20300	300
RC422-16	25	1	25.1	0.99	38.2	1.50	280	4060	1120	16240	340
RC422-20	31	1-1/4	31.6	1.24	49.1	1.93	210	3045	840	12180	460
RC422-24	38	1-1/2	37.7	1.48	55.5	2.19	185	2685	740	10740	560
RC422-32	51	2	50.6	1.99	68.8	2.71	165	2395	660	9580	660

合成橡胶内层，四层钢丝缠绕增强层，合成橡胶外层

Synthetic rubber tube, 4-spiral wire reinforcement, and synthetic rubber cover.

工作温度范围
-40°C-100°C

Operating Temperature Range:
-40°C-100°C

推荐使用介质
适于输送液压流体如醇、液压油、燃油、润滑油、乳化液、烃等

Application:
fluid transfer, such as alcohols, hydraulic oils, fuel, lubricating oils, emulsified liquid, hydrocarbon, and etc.

联系大连捷瑞流体控制股份有限公司获取更多信息
For more information, please contact JIERUI

